

## TECHNICAL DATA SHEET



## KRASO® Floor Penetration


### Product image



### Product information

item	<b>KRASO® Universal Funnel</b>
pressure resistance (bar)	7.0
weight (kg)	1.1
item no.	KUT110

### Technical drawing



### Dimensions

DN	nominal size	110
L	total length (mm)	222
ID	Ø funnel inside (mm)	260
SF	trowel flange (mm)	35
AV	Ø 4 Seal outside (mm)	190

### Application area

For installation in waterproof basements for connecting KG/HT pipes with offset and for connection to KG/KG2000 underground pipes, with water pressure tight, surrounding, thermally welded KRASO® 4 seal, spigot end on one side, non-slip building protection cover and additional protective cover.  
 Connection options! The surrounding flange with a diameter of 330 mm and its textured surface is ideal for connecting adhesive films and bitumen membranes. A screwable stainless steel clamping flange for a fixed/loose flange construction is optionally available for non-adhesive foils.

### Material

basic body	PP (solid wall material)
4 Seal	TPE
lip seal	SBR

### Tests

MPA	yes
DVGW	-

### Certificates

[check our download area](#)

### Resistance

temperature	-20°C up to 90°C
slurry	no
oil / petrol	no
ring stiffness	SN 10