## Junction box 120 mm air-tight













## Junction box Ø 120 mm O-range ECON®, air-tight, Depth 65 mm

- · Air-tight design with sealing membranes
- · for 2 electrical circuits through separator wall 9073-20
- · receptacle for TS 35 standard rail
- · with stable holding ring
- Cutting the installation opening with bi-metal cutter 1082-20 or VARIOCUT 1089-00
- · including cover and screws

Article no:	9273-91
EAN:	4013456548800
For panel thickness	7 - 40 mm
Depth	65 mm
Cut hole Ø	120 mm
Tube entries up to M25	6
Cable entries 3 x 2.5 mm <sup>2</sup> or 5 x 1.5 mm <sup>2</sup>	6
Cable entries 5 x 2.5 mm <sup>2</sup> or 7 x 1.5 mm <sup>2</sup>	4
Cable entries 3 x 1.5 mm <sup>2</sup>	6
Air-tight	Yes
Dispatch	10

Air-tight  $\emptyset$  120 mm junction box with ECON® technology for an energy-efficient electrical installation in accordance with GEG. Extremely easy fitting thanks to toolless cable and conduit entry. The sealing membranes guarantee permanent air-tightness and at the same time retention of the cable or conduit. The large box volume provides plenty of installation space for various cable connections.

- · Installation in Ø 120 mm cut hole
- · Elastic sealing membrane for guaranteed air-tightness
- · Toolless cable and conduit entry

O∙range ECON® tight









