

Drip edge profile EJOT® Pro TKP

TKP05/01: 8809012040

Application

Profile with drip edge, plug-in connector and glass fiber mesh to create an exact and stable plaster finish with targeted water flow for balcony and lintel soffits, insulated passageways, roller shutter boxes that can be plastered over, plinth connections without profiles, etc.

Properties

Targeted drainage of water; precise and clean plaster finish; Rectangular plug-in connector ensures flush and plumb edges; better plaster grip due to grooved surface

Storage and transport

lying on the entire surface; dry and frost-free; not above 50 °C; no direct sunlight

Dimensions and packaging

Bar length [m]	2
Pieces / cardboard box	25
Running meter / cardboard box	50
Cardboard box / pallet	36
Running meter / pallet	1,800
Pallet height [m]	1.3

Basic profile

Raw material	Rigid PVC – free from lead and cadmium – REACH compliant
Tolerances	Profile general tolerances 2A according to DIN 16941
Colour fastness	According to DIN EN 20105-A03 – compliance level 2

Mesh

Glass fiber fabric	R131 or comparable (certified on the basis of EAD 040016-01-0404 / EAD 040083-00-0404)
Fabric grammage [g/m²]	160
Mesh size [mm]	4 x 4
Fabric colour/print	White neutral
Fabric width [cm]	12.5 ± 5 %
Fabric fastening	welded

