

| Specifications | | | | |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------------|-------------|
| Item no. | Description | Quantity | Price per unit | Total Price |
| | <p>Supply and installation of single-sided tape for indoor use, type SEAL BAND</p> <p>Composition:</p> <ul style="list-style-type: none"> – Support in hydrorepellent impregnated paper, solvent-free acrylic glue and separation layer with double liner to facilitate laying <p>Characteristics:</p> <ul style="list-style-type: none"> – Application temperature (°C) : >-10 – VOC emissions (% (class A+)) : 0 <p>Can be applied to various smooth supports such as wood and OSB panels without further treatment of the surfaces. Surfaces should be dry and free of dust and solvents, grease or oil. The use of PRIMER is recommended for rough surfaces such as untreated OSB panels. After partially removing the separation layer, the tape can be applied easily and accurately in the corner point without further corrections. The seal is completed by removing the remaining film and sticking the tape to the support.</p> | | | |