

Declaration of performance

Wetguard 200 SA

8220-156050/8220-078050/8220-039050 – Vers.2.0

Nr. DoP-21-822-00

1. Unique identification code of the product-type

8220-156050
8220-078050
8220-039050

2. Product labeling

Wetguard 200 SA

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer

Weatherproofing during the construction phase
Vapour control layer
Flexible sheets for waterproofing - Plastic and rubber vapour control layers - EN 13984:2013

4. Name and contact address of the manufacturer

SIGA Cover AG
Rüt mattstrasse 7
6017 Ruswil
Switzerland

5. Name of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2

-

6. System of assessment and verification of constancy of performance of the construction product

AVCP System 3

7. Notified body

TECHNICKY A SKUSOBNY USTAV STAVEBNY n.O.
NB 1301
Haben die Bewertung und Überprüfung nach System "3" vorgenommen und Prüfberichte ausgestellt.

8. Declared Performance

Essential characteristics	Performance	Bottom tolerance	Top tolerance	Unit	Test Standard EN 13984:2013
Length	50	50	50.2	m	EN 1848-2
Width	1560	1555	1565	mm	EN 1848-2
	780	775	785		
	390	385	395		
Mass per unit area	260	220	280	g/m ²	EN 1849-2
Reaction to fire	E			class	EN 13501-1
Resistance to water penetration	W1			class	EN 1928
Water vapour transmission Sd-Value	3.5	2.5	4.5	m	EN 1931

Tensile property max. force (MD)	160	120	200	N/50mm	EN 12311-2
Tensile property max. force (CD)	120	80	160	N/50mm	EN 12311-2
Tensile property elongation (MD)	80	40	110	%	EN 12311-2
Tensile property elongation (CD)	80	40	110	%	EN 12311-2
Resistance to tearing (nail tearing) (MD)	80	60	100	N	EN 12310-1
Resistance to tearing (nail tearing) (CD)	90	65	115	N	EN 12310-1
Sd-Value After artificial ageing	passed				EN 1296 EN 1931
Chemical resistance Resistance to alkali	NPD				EN 1847 EN 12311-2
Resistance to impact	NPD				EN 12691
Shear resistance of joints	NPD				EN 12317-2
Hazardous substances	none				

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance (DOP) is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Seline Zürcher – Quality Management



Ruswil, 07.12.2022