

Corner bead EJOT® Pro GEW

GEW0812: 8801042540 | GEW1015: 8801012540 | GEW1023: 8801022540

Application

The corner bead serves as corner reinforcement and for the exact and perpendicular formation of 90 ° building corners and edges as well as door and window reveals.

Properties

Precise formation and protection of the facade edge; optimum incorporation into the system thanks to perforated profile design; impact-resistant and shatter-proof; alkali-resistant

Storage and transport

lying on the entire surface; dry and frost-free; not above 50 °C; no direct sunlight

Dimensions and packaging

Bar length [m]	2.5
Pieces / cardboard box	50
Running meter / cardboard box	125
Cardboard box / pallet	GEW0812: 45 GEW1015: 45 GEW1023: 36
Running meter / pallet	GEW0812: 5,625 GEW1015: 5,625 GEW1023: 4,500
Pallet height [m]	1.3

Basic profile

Raw material	Rigid PVC – free from lead and cadmium – REACH compliant
Tolerances	Profile general tolerances 2A according to DIN 16941
Colour fastness	According to DIN EN 20105-A03 – compliance level 2

Mesh

Glass fiber fabric	R131 or comparable (certified on the basis of EAD 040016-01-0404 / EAD 040083-00-0404)
Fabric grammage [g/m ²]	160
Mesh size [mm]	4 x 4
Fabric colour/print	White neutral
Fabric width [cm]	GEW0812: 8 x 12 ± 5 % GEW1015: 10 x 15 ± 5 % GEW1023: 10 x 23 ± 5 %
Fabric fastening	bonded

